



**GVW (lbs.)** 19,500  
**AXLE CAPACITY (lbs.)** Front 7,280 / Rear 13,660  
**SPRING CAPACITY (lbs.)** Front 8,000 / Rear 19,000  
**ENGINE (Hino)** J08E-VC Diesel, 6-cylinder  
 In-line, turbo intercooled, 7.6L  
**MAX. OUTPUT (HP)** 220 @ 2,500 rpm  
**MAX. TORQUE (lb.-ft.)** 520 @ 1,500 rpm  
**TRANSMISSION** 6-speed Allison 1000 RDS  
**SERVICE BRAKES** Hydraulic disc front and rear  
**WHEELS** 19.5 inch x 6.75 inch, 8 stud disc  
**TIRE SIZE** 225/70R19.5

**WHEELBASE CODES\***

	G	J	L	M
<b>WB</b>	152.0	175.0	187.0	205.0
<b>CA</b>	84.6	107.6	119.6	137.6

## 2013 Model 198



**GVW (lbs.)** 25,500  
**AXLE CAPACITY (lbs.)** Front 8,000 / Rear 17,500  
**SPRING CAPACITY (lbs.)** Front 8,000 / Rear 19,000  
**ENGINE (Hino)** J08E-VC Diesel, 6-cylinder  
 In-line, turbo intercooled, 7.6L  
**MAX. OUTPUT (HP)** 220 @ 2,500 rpm  
**MAX. TORQUE (lb.-ft.)** 520 @ 1,500 rpm  
**TRANSMISSION** 6-speed Allison 2200 RDS  
**SERVICE BRAKES** Hydraulic disc front and rear  
 Full air disc front and rear  
*(available on P & T wheel base)*

**WHEELS** 19.5 inch x 6.75 inch, 8 stud disc  
**TIRE SIZE** 245/70R19.5

**WHEELBASE CODES\***

	L	M	P	R	T	V
<b>WB</b>	187.0	205.0	217.0	235.0	253.0	271.0
<b>CA</b>	119.6	137.6	149.6	167.6	185.6	203.6

MKLINEUP13E

Truck shown with optional equipment.

## 2013 Model 258LP



# 2013

[www.hinocanada.com](http://www.hinocanada.com)





Truck shown with optional equipment.

**GVW (lbs.)** 26,000  
**AXLE CAPACITY (lbs.)** Front 10,000 / Rear 19,000  
**SPRING CAPACITY (lbs.)** Front 12,000 / Rear 19,000  
**ENGINE (Hino)** J08E-VC Diesel, 6-cylinder  
 In-line, turbo intercooled, 7.6L  
**MAX. OUTPUT (HP)** 220 @ 2,500 rpm  
**MAX. TORQUE (lb.-ft.)** 520 @ 1,500 rpm  
**TRANSMISSION** 6-speed Allison 2200 RDS  
**SERVICE BRAKES** Hydraulic disc front and rear  
 Full air disc front and rear  
*(available on T wheel base)*  
**WHEELS** 22.5 inch x 8.25 inch, 10 stud disc  
**TIRE SIZE** 11R22.5  
**WHEELBASE CODES\***

	L	M	P	R	T	V
<b>WB</b>	187.6	205.0	217.0	235.0	253.0	271.0
<b>CA</b>	119.6	137.6	149.6	167.6	185.6	203.6

## 2013 Model 268



Truck shown with optional equipment.

**GVW (lbs.)** 33,000  
**AXLE CAPACITY (lbs.)** Front 12,000 / Rear 21,000  
**SPRING CAPACITY (lbs.)** Front 12,000 / Rear 21,000  
**ENGINE (Hino)** J08E-VB Diesel, 6-cylinder  
 In-line, turbo intercooled, 7.6L  
**MAX. OUTPUT (HP)** 260 @ 2,500 rpm  
**MAX. TORQUE (lb.-ft.)** 660 @ 1,500 rpm  
**TRANSMISSION** 6-speed Allison 2500 RDS  
**SERVICE BRAKES** Hydraulic disc front and rear  
**WHEELS** 22.5 inch x 8.25 inch, 10 stud disc  
**TIRE SIZE** 11R22.5  
**WHEELBASE CODES\***

	L	M	P	R	T	V
<b>WB</b>	187.6	205.0	217.0	235.0	253.0	271.0
<b>CA</b>	119.6	137.6	149.6	167.6	185.6	203.6

## 2013 Model 338



Truck shown with optional equipment.

**GVW (lbs.)** 35,000  
**AXLE CAPACITY (lbs.)** Front 14,000 / Rear 23,000  
**SPRING CAPACITY (lbs.)** Front 14,000 / Rear 23,000  
**ENGINE (Hino)** J08E-VB Diesel, 6-cylinder  
 In-line, turbo intercooled, 7.6L  
**MAX. OUTPUT (HP)** 260 @ 2,500 rpm  
**MAX. TORQUE (lb.-ft.)** 660 @ 1,500 rpm  
**TRANSMISSION** 6-speed Allison 3000 RDS  
**SERVICE BRAKES** Full air  
**WHEELS** 22.5 inch x 8.25 inch, 10 stud disc  
**TIRE SIZE** 11R22.5  
**WHEELBASE CODES\***

	L	M	P	R	T	V
<b>WB</b>	187.6	205.0	217.0	235.0	253.0	271.0
<b>CA</b>	119.6	137.6	149.6	167.6	185.6	203.6

## 2013 Model 358

\*See dealer for wheelbase availability

WB: Distance between the centerline of the front and rear axles  
 CA: Distance from the back of the cab to the centerline of the rear axle